



Model Number	Nominal Size (Inches) W x H x D	Actual Size (Inches) W x H x D	Rated Air Flow (CFM)	Initial Resistance (In. W.G.)	Media Area (Square Feet)
PR13-STD1	10 X 10 X 1	9-1/2 X 9-1/2 X 3/4	210	0.43	1.6
PR13-STD1	10 X 20 X 1	9-1/2 X 19-1/2 X 3/4	415	0.43	2.6
PR13-STD1	10 X 24 X 1	9-3/8 X 23-3/8 X 3/4	500	0.43	3.1
PR13-STD1	12 X 12 X 1	11-3/4 X 11-3/4 X 3/4	300	0.43	1.9
PR13-STD1	12 X 16 X 1	11-1/2 X 15-3/4 X 3/4	400	0.43	2.5
PR13-STD1	12 X 20 X 1	11-1/2 X 19-1/2 X 3/4	500	0.43	3.1
PR13-STD1	12 X 24 X 1	11-3/8 X 23-3/8 X 3/4	600	0.43	3.7
PR13-STD1	14 X 14 X 1	13-3/4 X 13-3/4 X 3/4	410	0.43	2.7
PR13-STD1	14 X 20 X 1	13-1/2 X 19-1/2 X 3/4	585	0.43	3.8
PR13-STD1	14 X 24 X 1	13-3/8 X 23-3/8 X 3/4	700	0.43	4.6
PR13-STD1	14 X 25 X 1	13-1/2 X 24-1/2 X 3/4	730	0.43	4.8
PR13-STD1	14 X 30 X 1*	14-3/4 X 29-3/4 X 3/4	875	0.43	5.7
PR13-STD1	15 X 20 X 1	15-1/2 X 19-1/2 X 3/4	625	0.43	4.0
PR13-STD1	15 X 30 X 1*	15-3/4 X 29-3/4 X 3/4	935	0.43	6.1
PR13-STD1	16 X 16 X 1	15-1/2 X 15-1/2 X 3/4	530	0.43	4.0
PR13-STD1	16 X 20 X 1	15-1/2 X 19-1/2 X 3/4	665	0.43	4.3
PR13-STD1	16 X 24 X 1	15-3/8 X 23-3/8 X 3/4	800	0.43	5.1
PR13-STD1	16 X 25 X 1	15-1/2 X 24-1/2 X 3/4	835	0.43	5.3
PR13-STD1	16 X 30 X 1*	15-3/4 X 29-3/4 X 3/4	1000	0.43	6.5
PR13-STD1	18 X 18 X 1	17-3/4 X 17-3/4 X 3/4	675	0.43	4.3
PR13-STD1	18 X 20 X 1	17-3/8 X 19-1/2 X 3/4	750	0.43	4.8
PR13-STD1	18 X 22 X 1	17-3/8 X 21-1/2 X 3/4	825	0.43	5.7
PR13-STD1	18 X 24 X 1	17-3/8 X 23-3/8 X 3/4	900	0.43	5.7
PR13-STD1	18 X 25 X 1	17-1/2 X 24-1/2 X 3/4	935	0.43	6.0
PR13-STD1	20 X 20 X 1	19-1/2 X 19-1/2 X 3/4	830	0.43	5.5
PR13-STD1	20 X 22 X 1	19-3/4 X 21-3/4 X 3/4	915	0.43	6.6
PR13-STD1	20 X 24 X 1	19-3/8 X 23-3/8 X 3/4	1000	0.43	6.6
PR13-STD1	20 X 25 X 1	19-1/2 X 24-1/2 X 3/4	1040	0.43	6.9
PR13-STD1	20 X 30 X 1*	19-1/2 X 29-1/2 X 3/4	1250	0.43	7.1
PR13-STD1	22 X 22 X 1	21-3/4 X 21-3/4 X 3/4	1005	0.43	8.1
PR13-STD1	24 X 24 X 1	23-3/8 X 23-3/8 X 3/4	1200	0.43	7.7
PR13-STD1	24 X 30 X 1*	23-3/4 X 19-3/4 X 3/4	1500	0.43	9.7
PR13-STD1	25 X 25 X 1	24-1/2 X 24-1/2 X 3/4	1300	0.43	8.7

* Reverse pleat direction

STANDARD CONSTRUCTION

- 100% Synthetic White Un-Dyed Media
- 14.0 Pleats Per Foot
- Expanded Metal Pleat Supports
- Moisture Resistant Beverage Board Frame
- Double Wall Frame

NOTES

- MERV 13 Per ASHRAE 52.2-2012
Tested at 295 FPM on 24x24x1 filter size
- Final Resistance: 1.0" W.G.
- Rated Velocity: 300 FPM
- Classified Per UL Standard 900 for Flammability
- Maximum Operating Temperature: 225 deg. F

Purolator
 100 River Ridge Circle
 Jeffersonville, IN 47130
 P: 866-925-2247
 F: 866-601-1809
 www.clc.air.com/purolator

CONTACT FACTORY TO
 VERIFY REVISION LEVEL

**TOLERANCES
 UNLESS OTHERWISE SPECIFIED**

FRACTIONAL —
 DECIMAL —
 ANGLES —

ALL DIMENSIONS IN INCHES

DRAWING NAME

PURO-G13EEN (1" DEPTH)

APPROVED BY

K. Quinn

SPECIFICATION NO.

MKT-P-00577

PAGE

1 OF 1

SCALE

NONE

DWG. SIZE

A

REVISION

A

REVISION DATE

08-24-15

CONFIDENTIAL - DO NOT COPY. THIS MATERIAL IS TRADE SECRET AND PROPRIETARY BEING EXCLUSIVELY OWNED BY CLC AIR. THE EXPRESSION OF THE INFORMATION CONTAINED HEREIN IS PROTECTED UNDER FEDERAL COPYRIGHT LAWS AND ALL COPYING IS PROHIBITED AND MAY BE SUBJECT TO CRIMINAL PENALTIES.