

-Parker


Interchange Element Data Sheet

Data sheet created using the Parker Par Fit Toolkit software.

| Creation Date: | 03/08/2018 |
|-----------------|----------------|
| Datasheet No: | DS345W |
| Parker Part No: | 932679Q |
| OEM: | Pall |
| OEM Part No: | HC9700FKS18H&Z |

Product Dimensions

| A (mm) | 99.0 | (inch) | 3.90 |
|--------|-------|--------|-------|
| B (mm) | 42.0 | (inch) | 1.65 |
| C (mm) | 42 | (inch) | 1.65 |
| D (mm) | 99.0 | (inch) | 3.90 |
| E (mm) | 470.0 | (inch) | 18.50 |





Construction Materials

| Seal(s): | FPM: Fluoroelastomer |
|-------------------------|--|
| Top Endcap: | Glass reinforced nylon |
| Bottom Endcap: | Glass reinforced nylon |
| Inner Support Cylinder: | Mild steel tin plated |
| Filter Media: | Multilayer fibreglass with coated mesh on both sides |

Calculated Performance Criteria

| | Pressure (∆p): 6O3968 @ 32 cSt | 0.32 bar @ 1200 l/min 4.64 psi @ 263.96 gp | | |
|--|-----------------------------------|---|--|--|
| Efficiency: >Beta 200 @ 10 microns & greater >Beta 1000 @ 12 microns & greater | | | | |
| Minimum Collapse Pressure: Tested to ISO2941 | | >10 bar >145 psi | | |
| Dirt Holding Capacity acc. to ISO16889 >178.2 gram @ 5 bar terminal pressure drop | | | | |

>178.2 gram @ 73 psi terminal pressure drop



ENGINEERING YOUR SUCCESS.

www.parker.com/parfit