

## DRYER DATA SHEET

### Refrigerant Dryers

MODEL DATA				
1	Manufacturer	Parker		
2	Date	3/28/2016		
3	Model Number	PNC400		
4	Cycling/Non-Cycling	Non- Cycling		
5	Refrigerant Type	R404A		
	DESCRIPTION	FULL FLOW	10% FLOW	UNITS
6	Tested Flow <sup>a</sup>	400	40	scfm <sup>b</sup>
7	Outlet Pressure Dewpoint	39	39	°F
8	Pressure Drop	2.8	0.2	psi(d)
9	Total Dryer Input Power	2.66	2.41	kW
10	Specific Package Power <sup>c</sup>	0.67	6.03	kW/100 scfm

Notes:

- a. Dryer ratings at the following inlet conditions to the dryer (as per adopted CAGI Standard ADF 100):

Inlet Compressed Air Temperature:	100°F (37.78°C)
Inlet Compressed Air Pressure:	100 psig (6.9 Bar)
Max. Ambient Air Temperature:	100°F (37.78°C)
Inlet Compressed Air Relative Humidity	100% (Saturated)

- b. SCFM defined as the volume of free air in cubic feet per minute measured at 14.5 psia (1.0 Bar), 68°F (20°C) temperature and 0% R.H. (0 WVP).

- c.  $(\text{Total Dryer Input Power}/\text{tested flow}) \times 100$



This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.

Consult the CAGI website, [www.cagi.org](http://www.cagi.org), for a list of participants in the third party verification program.

Form Number REF 010